

09/23/99



jc447 U.S. PTO

Please type a plus sign (+) inside this box →

Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 101141R
First Inventor or Application Identifier Kenneth L. Levy
Title Method & Apparatus For Embedding Auxiliary Information
Express Mail Label No. EM 441817625USwithin
Original
Data.**APPLICATION ELEMENTS**

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 42]
(preferred arrangement set forth below)
- Descriptive title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 9]
4. Oath or Declaration [Total Pages]
a. ☐ Newly executed (original or copy)
b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
a. ☐ Computer Readable Copy
b. ☐ Paper Copy (identical to computer copy)
c. ☐ Statement verifying identity of above copy

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☒ * Small Entity Statement(s) ☒ Statement filed in prior application, Status still proper and desired
(PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☒ Other: Assignment of Application

*** NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).****16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:**☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: Prior application information: Examiner Group / Art Unit: **For CONTINUATION or DIVISIONAL APPS only:** The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.**17. CORRESPONDENCE ADDRESS**☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☒ Correspondence address below

Name Kenneth Levy
AIPL

Address 110 NE Cedar Street

City Stevenson State WA Zip Code 98648

Country USA Telephone 509-427-5374 Fax 509-427-7101

Name (Print/Type) Ken Levy Registration No. (Attorney/Agent)

Signature [Signature] Date 9/22/1999

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

**STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(b))--INDEPENDENT INVENTOR**

Docket Number (Optional)

Levy IR

Applicant, Patentee, or Identifier: Kenneth L. Levy

Application or Patent No.: _____

Filed or Issued: _____

Title: Method And Apparatus For Embedding Auxiliary Information Within Original Data.

As a below named inventor, I hereby state that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees to the Patent and Trademark Office described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

I have not assigned, granted, conveyed, or licensed, and am under no obligation under contract or law to assign, grant, convey, or license, any rights in the invention to any person who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☐ No such person, concern, or organization exists.
☒ Each such person, concern, or organization is listed below.

Acoustic Information Processing Lab, LLC
110 NE Cedar Street
Stevenson, WA 98648

Separate statements are required from each named person, concern, or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

Kenneth L. Levy
NAME OF INVENTOR

NAME OF INVENTOR

NAME OF INVENTOR

[Signature]
Signature of inventor

Signature of inventor

Signature of inventor

Date

9/22/99

Date

Date

**STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(c))--SMALL BUSINESS CONCERN**

Docket Number (Optional)

Levy IR

Applicant, Patentee, or Identifier: Kenneth L. Levy
Application or Patent No.: _____
Filed or Issued: _____
Title: Method And Apparatus For Embedding Auxiliary Information Within Original Data.

I hereby state that I am

- ☐ the owner of the small business concern identified below:
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF SMALL BUSINESS CONCERN Acoustic Information Processing Lab, LLC

ADDRESS OF SMALL BUSINESS CONCERN 110 NE Cedar Street, Stevenson, WA, 98648

I hereby state that the above identified small business concern qualifies as a small business concern as defined in 13 CFR Part 121 for purposes of paying reduced fees to the United States Patent and Trademark Office. Questions related to size standards for a small business concern may be directed to: Small Business Administration, Size Standards Staff, 409 Third Street, SW, Washington, DC 20416.

I hereby state that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

If the rights held by the above identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate statements as to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization having any rights in the invention is listed below:

- ☒ no such person, concern, or organization exists.
☐ each such person, concern, or organization is listed below.

Separate statements are required from each named person, concern or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

NAME OF PERSON SIGNING Kenneth L. Levy

TITLE OF PERSON IF OTHER THAN OWNER President

ADDRESS OF PERSON SIGNING AIPL, 110 NE Cedar St, Stevenson, WA 98648

SIGNATURE [Signature] DATE 9/22/99

METHOD AND APPARATUS FOR EMBEDDING
AUXILIARY INFORMATION WITHIN ORIGINAL DATA

This application claims the benefit of Provisional
5 Patent Applications Ser. #60/101,851 filed 9/25/98,
#60/110,683 filed 12/02/98, #60/114,725 filed 12/31/98,
and #60/126,591 filed 3/26/99, incorporated herein by
reference.

This application relates to Provisional Patent
10 Applications Ser. #60/123,587 filed 3/10/99 and
#60/126,592 filed 3/26/99, incorporated herein by
reference. The application also relates to Utility
Patent Application Ser. #_____ filed on 9/23/99
(the same date as this application) entitled "Method
15 and apparatus for robust embedded data" by the same
author as this application, Kenneth L. Levy,
incorporated herein by reference.

Field of the Invention

20 This invention relates to the field of signal
processing, and more specifically, to techniques for
hiding auxiliary information within original data.

Background of the Invention

25 With the recent explosive growth in the use of
electronic information, enforcement of copyright laws
has become more difficult. The cost of the equipment
required to copy digital data representing music, art,
and other valuable information has been decreasing,
30 while the capacity of readily available data storage
media has been increasing. Inexpensive devices can
write enormous amounts of data to digital storage media
such as writable compact disks (CD-R or CD-RWs), multi-
gigabyte hard disk drives, high capacity removable
35 magnetic disks, and soon to be available digital

versatile disks (DVDs). Readily available high-resolution printers and scanners bring the digitization and reproduction of graphic information within the means of most consumers. In addition, readily
5 available high-resolution sound cards, including analog-to-digital and digital-to-analog converters, bring the digitization and reproduction of audio information within the means of most consumers. Not only is copying digital files simple and inexpensive,
10 the Internet facilitates unauthorized distribution of copyrighted works.

Unlike analog copies, which are always inferior to the original, a copy of digital information can be identical to that of the original, with no degradation
15 due to copying. Millions of dollars are lost annually due to illegal but exact duplications of digital media and near-exact duplications of analog media. Because copying equipment is readily available, catching persons making unauthorized copies can be difficult.
20 Even if an unauthorized copier is apprehended, the creator of the original document must still prove that the allegedly unauthorized copy was in fact copied from his original work and not independently created.

One approach to solving the problem of illegal
25 copying is embedding or hiding authentication information or copy protection information within the original data. Hiding auxiliary information in original data, also called steganography, has been used for thousands of years. In steganography, a message is hidden within
30 another object or media, so that the message is minimally perceived by an observer. Steganography is related to, but different from, cryptography, in which the existence of a message is typically obvious, but its meaning is not ascertainable without special
35 knowledge.

Hidden data, also referred to as auxiliary or embedded data, can be used to prevent unauthorized copying by embedding in the original data commands that are readable by the copying device and that instruct the copying device not to make a usable copy. Hidden data can also be used to authenticate data, that is, to prove authorship. One such technique entails embedding auxiliary information in an original work in such a manner that special knowledge, such as a secret algorithm or code, is required to detect and/or remove the auxiliary information. The copier would not be able to remove the authentication information, and the original creator could prove his authorship by retrieving the embedded information, which would identify him as the author.

Data hiding has uses besides the prevention and detection of unauthorized copying. One such use is content enhancement, that is, adding information to the original data to enhance the content. For example, lyrics could be embedded in audio data on a CD. The lyrics could be viewed in a special kareoke machine, while the audio could be played on an existing CD player. Hidden data could also be used to associate different segments of video data with different viewer-selectable versions of the video on a DVD. For example, a viewer could select between a version edited for children or an unabridged version, and embedded auxiliary data would indicate to the DVD player which video segments to skip and which to include for the selected version.

The original data in which the auxiliary data is hidden may represent any type of information that is perceivable with the aid of a presenting device. For example, the data may represent music which is presented using a compact disk or audio DVD player, a video film

that is presented on a DVD player, or an image that is presented on a computer screen or a printer.

When the combined data is presented to a user by a normal presentation device, the auxiliary data should not interfere with the use of the original data. Ideally, the user should not be able to perceive the auxiliary data at all. Unfortunately, increasing the amount of the embedded auxiliary data or its robustness, that is, its persistence to attack and data transformation, may incidentally increase its perceptibility. The degree to which the auxiliary data can be perceived without having an adverse impact on the user varies with the application. For example, in CD quality audio, a minor change from the original data might result in unacceptable audio artifacts. In video data, a minor change in a presented image may be acceptable, even though the change might be noticeable if the original and combined works are presented and compared side by side.

Several techniques are known for hiding auxiliary information in original digital data. Data can be hidden in original data as headers or trailers appended to the original data. Such techniques are of limited use in protection of copyrighted works, because the auxiliary data is easily located and stripped out of the copy, as when changing format. More sophisticated techniques distribute the auxiliary data through the original data, entwining the auxiliary and original data until the auxiliary data is difficult, or even statistically impossible, to identify and strip from the combined data.

Most data hiding techniques that distribute the auxiliary data through the original data are computationally intense and therefore expensive to implement. Many of these techniques are based upon

adding or subtracting periods of pseudo-random noise (PN) sequences with the signal to represent the auxiliary information, and these sequences may require filtering (a.k.a. shaping) in the frequency domain.

- 5 The rest are based upon adding the auxiliary information to the original data after the original data has been transformed into the frequency domain, such as by a Fourier transform. Auxiliary information can be added in the frequency domain so that the energy
- 10 of the auxiliary data is spread across many frequencies in a manner similar to that of the PN sequence. In addition, auxiliary information can be added to the phase of the frequency components with and without spreading the information across frequencies.
- 15 Unfortunately, transforming the data into the frequency domain and/or shaping the energy of the PN sequence so it is less perceivable requires intense calculations.

- The ability of users to detect auxiliary data depends not only upon the data, but also upon the
- 20 characteristics of the human sense organs and the interpretation of sensory stimuli by the brain. Some data hiding techniques transform the original data into the frequency domain and embed auxiliary data in a manner such that the frequency spectrum of the original
- 25 data reduces the perception of embedded data. This psychophysical effect is known as masking. The frequency distribution of the original data is used to determine preferred frequencies at which the embedded auxiliary data will be less perceptible, that is,
- 30 masked. Others use the fact that we don't perceive phase as accurately as magnitude in the frequency domain.

- There are some data embedding techniques that are less computationally intense and that still distribute
- 35 the auxiliary data in the original data. Such

techniques include amplitude modulation, frequency band elimination, distinct quantization, and least-significant bit (LSB) replacement. These techniques embed data in predetermined locations without regard to the original data and are, therefore, more likely to produce perceptual side affects in the combined data. In addition, the LSB replacement technique is easily disturbed by low level noise.

The ease of retrieving embedded data varies with the technique used for embedding. Some data hiding and retrieving techniques retrieve the auxiliary data by comparing the combined data with the original data: Others retrieve the auxiliary information using databases of the PN sequences that were originally used to hide the data. Techniques that require that a copy of the original data or a PN database be used to extract the auxiliary data are of limited use in applications in which the combined data is distributed broadly. Such techniques are useful in some applications, such as data authentication, in which the auxiliary data is retrieved rarely and only by the copyright owner.

Thus, it would be desirable to have a data hiding and extracting technique that is not computationally intense and that maintains a desired level of perceptibility and robustness, and in which the embedded data that can be retrieved from the combined data without access to the original data.

Summary of the Invention

Accordingly, it is an object of the present invention to provide a method and apparatus of data hiding and retrieval.

An advantage of the present invention is its extreme efficiency relative to the prior art. Thus,

the apparatus is less expensive.

Another advantage of the invention is that it does not require the original file or other database for extracting the auxiliary data.

5 Another advantage of the invention is that it uses an adaptive algorithm based upon psychophysics. Specifically, the invention uses the original data; in unmodified form or without complex data transformations, to determine the location to insert auxiliary
10 data.

A further advantage of the invention is that, in some embodiments, the embedded data can be imperceptible when presented with existing players.

Still another advantage of the invention is that
15 usually it uses a broadband approach that distributes the auxiliary data through the original data, thereby making the auxiliary data more difficult to detect and remove.

Yet another advantage of the invention is that it
20 provides for a minimal decrease in signal-to-noise ratio (SNR) of the combined data as compared to the original data.

Still a further advantage of the invention is that it provides non-LSB capabilities, thereby providing
25 increased robustness, that is, the auxiliary data is unchanged by some transformations of the combined data.

Yet a further advantage of the invention is that it can cause no detectable change in data's statistics, thereby making authentication information impossible to
30 identify.

Still another advantage of the invention is its versatility, in that it allows the user to set parameters that vary the perceptibility, robustness, and embedding rate so that the invention can be used in
35 a broad variety of applications.

The apparatus for the present invention includes a logic processor and storage unit, such as those that come with the standard computer or on DSP boards. These devices will act as data readers, comparer and data writers, such the user's desired watermark can be embedded and/or retrieved.

The process involves embedding and retrieving auxiliary information into original data to produce combined data. The invention uses a detection criterion or criteria to determine where in the original data to locate and adjust data points to carry the auxiliary information. The detection criteria is used to locate positions, referred to as local masking opportunities, in the original data at which the embedding of auxiliary data will produce less perception, as compared to other simplistic processes.

When embedding the auxiliary data, the data points in the original data are investigated in accordance with the detection criteria to determine the existence of local masking opportunities. The detection criterion or criteria may involve, for example, comparing the data point to a predetermined value and examining the relationship of the data point to nearby points. If the detection criteria are met, one or more of the nearby points, or the data point being investigated, is changed to indicate the value of an embedded bit of auxiliary data.

Thus, although the search for local masking opportunities typically progresses point by point through the data, the investigation of each point may include not only the value of that point, but also values of one or more nearby points and/or one or more relationships among the points. If the investigation of a point shows the existence of a local masking opportunity, data is embedded by setting the value of

one or more of the local points, that is, either the point being investigated or one or more of the nearby points.

The value to which the nearby data points are set is typically dependent upon the data point being investigated as well as on the value of the auxiliary data bit. The data point value can be set so that it has a specified relationship with the neighboring data points. The process is continued until the original data has been traversed or no additional auxiliary data remains to be embedded.

Retrieving the auxiliary data is the inverse of the embedding process. The combined data is traversed using the detection criteria to locate the local masking opportunities. As each local masking opportunity is located, the nearby data point or points that was or were set to indicate the embedded bit is or are read to extract the embedded data. The process is continued until the combined data has been traversed.

In the preferred embodiments, a data point or points are set to a value relative to the nearby data points and not to an absolute value. Both setting data points at the local masking opportunity and setting the data point to a value related to the nearby points, rather than to a value unrelated to the original data, provide masking that reduces the perceptibility of the data. The data is extracted by determining the relationships or values of the point or points near the local masking opportunity.

For the two preferred embodiments described in detail below, only points with large values are adjusted, and by a minimal amount; thus, these embodiments are based upon the masking of a weak stimulus by an intense stimulus. The process is applicable to analog and digital data. However, both

embodiments are explained in terms of digital media due to current switch to digital media and the ease of understanding.

Specifically, the first preferred embodiment uses
5 the difference between a data point after a peak and the peak level to carry auxiliary information, as long as the peak is above a large threshold and the original difference between the peak and next point is not too great. This large threshold and minimal differences
10 produce the desired perceptual masking. The embedding process adjusts the point after the above-threshold peaks to hide the auxiliary data. Correspondingly, the retrieving process measures the difference between each above threshold peak level and the next data point to
15 retrieve the auxiliary data.

The second preferred embodiment uses the change in slope across a positive, large, steep, threshold
crossing to hide the auxiliary information, as long as the original change in slope is not too great yet steep
20 enough to accept the ensuing adjustment. Again, the large threshold produces the desired perceptual masking. In the implementation, the embedding process adjusts the change in slope to embed the data, whereas the retrieving process measures the change in slope to
25 obtain the auxiliary data.

Usually, the preferred embedding process implicitly spreads the energy of the auxiliary information throughout the original data. This broadband approach produces data that is more difficult
30 to remove than sub-band approaches that place the data in an inaudible frequency range. If desired, parameters can be chosen so that the process produces protected data that is statistically identical to unmarked data. Importantly, the process can be
35 adjusted to produce the desired tradeoffs between

perception, coding rate and robustness to attack.

Such embodiments of the invention preferably operate on the original data without requiring any complex data transformations, such as a Fourier transformation. Thus, if the original data represents information in the time domain, the data can remain in the time domain as the auxiliary data is embedded and retrieved. Of course, the invention can operate on original data of all types, such as in the frequency or time-frequency domain. For example, it can be applied to MPEG data, including the MPEG 1 and 2 specification, ISO 11172-3 and ISO 13818-7 respectively, herein by reference, which exists in the time-frequency domain.

Finally, the problem of bit-rate reducing techniques, known as compression, removing the watermark can be bypassed by using separate, but possibly identical, watermark procedures during the compression (a.k.a. encoding) and decompression (a.k.a. decoding) process.

In summary, the present invention has the advantage of being extremely efficient to implement while still maintaining a desired level of robustness, i.e., resistance to tampering, including non-LSB (least significant bit) capabilities and statistical invisibility. The efficiency of the present invention means that it is cheaper to implement and can be used to embed, retrieve and search more files than a computationally intense algorithm. Further objects and advantages will become apparent from a consideration of the ensuing description and drawings.

Brief Description of the Drawings

FIG. 1 is a flowchart showing, in general, the steps embedding data using the invention.

FIG. 2 is a block diagram showing an apparatus

used to embed or retrieve data using the process of FIG. 1.

FIG. 3 is a flowchart showing, in general, the steps used to retrieve the data embedded using the process of FIG. 1.

FIG. 4 graphically displays the operation of a first embodiment of the invention.

FIG. 5 is a flowchart showing the steps of embedding data in accordance with the first embodiment of the invention. The dashed lines show interaction with the auxiliary data.

FIG. 6 is a flowchart showing the steps of retrieving data that was encoded in accordance with the embodiment shown in FIG. 5. The dashed lines show interaction with the auxiliary data.

FIG. 7 graphically displays the operation of a second embodiment of the invention.

FIG. 8 is a flowchart showing the steps of embedding data in accordance with a second embodiment of the invention. The dashed lines show interaction with the auxiliary data.

FIG. 9 is a flowchart showing the steps of retrieving data that was encoded in accordance with the embodiment shown in FIG. 8. The dashed lines show interaction with the auxiliary data.

FIG. 10 demonstrates the operation of the invention in conjunction with digital compression techniques.

FIG. 11 A and B are two block diagrams showing an embedding and retrieving apparatus used to carry out the invention.

FIG. 12 shows an embodiment of the apparatus of FIG. 2 for embedding data.

FIG. 13 is a block diagram showing an embodiment of the apparatus of FIG. 2 for retrieving the data.

Detailed Description

The system according to a preferred embodiment of the present invention comprises a method and apparatus
5 for hiding auxiliary information (or data) in original data and for retrieving the auxiliary information.

FIG. 1 is an overview of the steps involved in carrying out a method of the invention to embed data. FIG. 2 shows a block diagram of an apparatus **10** used to
10 perform the method of FIG. 1. Apparatus **10** includes a logic processor **14**, which can be a general purpose microprocessor, such as an Intel Pentium or DEC Alpha, of the type a personal computer or engineering workstation, a digital signal processor (DSP), such the
15 hte Texas Instruments TMS320 line, a specialized CPU, such as a media processor, or a custom processing circuit. Apparatus **10** also includes a storage unit **18**, which can include random access memory (RAM) or delays. Because the algorithms used by the invention are not
20 computationally intense, they require calculations on the order of less than one million instructions per second and can be performed by most modern personal computers.

The original data mentioned below might represent
25 sound that is recorded by sampling its amplitude periodically, with each sample using binary numbers to represent the magnitude of the sound at a particular time. Alternatively, the original data could be any series of binary data associated into groups.
30 Similarly, the auxiliary information is any data that can be represented as "1"s and "0"s.

FIG. 1 shows that in step **20**, a portion of the original data is read into storage unit **18** of FIG. 2. Step **24** shows that the sample data is investigated
35 sequentially by the logic processor **14** to locate sample

points that meet predefined detection criteria. Such sample points indicate the existence of "local masking opportunities," because the detection criteria are such that a change in the value of the sample or a few samples at or near that point to embed auxiliary data will usually have minimal perceivable by the listener of the sound. The amount of masking will depend upon the data type and settings chosen by the user. For example, the masking will be great for uncompressed audio and less for bit-rate reduced (digitally compressed) audio such as MPEG. The same detection criteria will be applied during data retrieval to locate the hidden data.

Each point in the original data is preferably investigated to determine whether it represents a local masking opportunity. The criterion or criteria for determining local masking opportunities may entail not only the value of the point being investigated, but may also include the value of at least one nearby or neighboring point, or the relationship between the nearby point and the point being investigated. The detection criteria can require, for example, that the point being investigated exceeds a certain threshold value and/or that the point be a local maximum or peak. The criteria may include a requirement that a point subsequent to the point being investigated have a value that differs from the point being investigated by less than a prescribed amount, or have some other relationship to the point being investigated.

The sample data points can be considered as plotted on a graph, for example with time on the x-axis and the magnitude of the sample on the y-axis. Thus, the series of data points can be considered as having a slope between any points, and the value of the slope can be part of the detection criteria. The criteria

may specify, for example, that a slope defined by the point being investigated and a preceding point exceed a particular value, or that the change in slope before and after the point not exceeds a particular value.

- 5 The criteria could include any combination of requirements. The threshold criteria can be changed to meet the needs of specific applications without departing from the concept of the invention.

In each case, no complex data transformation is
10 required to mask the auxiliary data, so comparing a point to the detection criteria is relatively quick and inexpensive. Unlike prior art methods, which need to use distant points to convert the original data into the frequency domain to determine how to mask embedded
15 data, the present invention can determines masking opportunities using only nearby or neighboring points, that is, points that are too close to use to determine useful frequency data. Nearby points including points that are next to the point being investigated or within
20 a relatively small number of points, preferably less than 50 and more preferably less than 20. The criterion can be as simple as determining whether the point exceeds a threshold.

Step 26 shows that when a point meeting the
25 detection criteria is located, the value of a specified sample point or sample points near the local masking opportunity is changed to reflect the value of the auxiliary information to be embedded. Although the changed sample may be simply set to a particular value
30 to signify the value of the embedded bit, the new value typically depends upon the value of both the auxiliary data and the neighboring point or points that were investigated to detect the local masking opportunity. For example, the point may be set so that the change in
35 value or slope signifies whether the embedded bit is a

"1" or a "0".

When a point is set to its new value, it is important that either the change does not prevent the original sample point from continuing to meet the
 5 detection criteria, or that this local masking opportunity is skipped and not detected in the retrieval process. Otherwise, the embedded auxiliary data will not be retrievable.

Alternatively, it is possible to merely embed the
 10 auxiliary bit as the least significant bit, or other, preferably low order, bit. The embedded bit is still masked because the location of the embedded bit was chosen to represent a local masking opportunity, such as when the data is larger than a prescribed threshold.

15 Step **30** shows that the process is ended at step **32** if no additional auxiliary data needs to be embedded. Otherwise, step **34** shows that if there is additional data in memory, the search for local masking opportunities continues. Step **36** shows that if all
 20 data in memory has not yet been searched, additional data is read into memory. Skilled persons will recognize that some overlap of the data in memory is required to prevent missing local masking opportunities that occur at the beginning or end points of the data
 25 in memory.

FIG. 3 broadly shows the steps involved in carrying out a method of the invention to detect and retrieve the embedded auxiliary information. Because the same processor and memory that was used to embed
 30 the data can be used to retrieve the data, although not necessary, the steps of FIG. 3 will describe extracting data using the hardware components of FIG. 2. Step **50** shows that a portion of the original data is read into storage unit **18**. Step **52** shows that logic processor **14**
 35 investigates each data point to determine the existence

of a local masking opportunity. If a sample point meets the local masking opportunity criteria, step **54** shows that the embedded "1" or "0" bit of auxiliary data is extracted using the inverse relationship of how the auxiliary data was embedded. Step **56** shows that if additional combined data is in the memory, the logic processor continues to investigate the remaining points with step **52**. Step **58** shows that if all the data in memory has been investigated, but there is uninvestigated combined data in the data file, additional data is read into memory in step **50**. Step **60** shows that the process is ended when all the combined data has been investigated.

Two preferred embodiments are described briefly here, and in detail below, to demonstrate the flavor of this methodology. As shown in FIG. 4, the first embodiment uses large, positive peaks as the detection criteria **120** and the auxiliary information is stored in the difference **130** between the peak and the next point. As shown in FIG. 7, the second embodiment uses large, steep threshold crossings with minimal change in slope as the detection criteria **140**, and the auxiliary information **150** is carried in the change in slope.

The methodology is applicable to analog or digital data, even though the preferred embodiments use digital data. For example, analog data can be sampled at the Nyquist rate to produce digital data in which additional information is hidden. Then, the combined digital data can be returned to the analog domain by any existing method known in digital signal processing (DSP). The analog data now contains the embedded data, which can be decoded by using sampling. This is just one possible method to encode analog data with the above methodology.

The methodology is also applicable to audio,

speech, images, video or any other perceivable signal. With audio and speech, the original data could represent pressure versus time, magnitude versus frequency, or a specific frequency magnitude versus time. With images, the original data could represent gray code versus space, separate or combined RGB or equivalent values versus space, or magnitude versus frequency. Video data encompasses the image data with an added dimension of time available. For example, with MPEG bit-reduced audio or images the auxiliary data could be embedded in scaling factors or frequency coefficients versus frequency or time or both.

Usually one of the detection criteria is a large threshold. With 16 bit audio, a threshold greater than 48 dB above the minimum value is desirable. This threshold allows the data to be changed with minimal perception due to masking. Masking is the psychological term defined as the increase in threshold for steady-state stimuli. Use of the term in this invention is much broader than that definition, and describes how one set of data reduces the perception of other data. Specifically, for uncompressed, magnitude-time data, the sensitivity of the sensory system decreases with increased input level, thus the small adjustment of an neighboring data point is masked by the large value of the threshold. For bit-rate reduced, time-frequency data, such as MPEG data, the masking is minimal and more similar to the textbook definition since masking has been used to reduce the bit rate.

Finally, this method is applicable to data where masking is not used, but the efficiency of the process in that it does not require a key, such as a PN sequence, or original data for retrieval of the auxiliary information, is an advantage. In summary,

the parameters of the detection criteria will determine the interaction between the data rate, process complexity and perceptual quality.

5 *Embodiment 1*

The first preferred embodiment is based upon hiding the auxiliary information in large peaks within the original data. In this embodiment, the auxiliary information is preferably broken into N bit words, with
 10 synchronization data placed between the words for better error recovery. The auxiliary information does not need to include sync pulses between the words if robustness to noise or modified files is not needed.

FIG. 4 conceptually shows that the first
 15 embodiment detects a peak or local maximum and sets the value of the subsequent point in relation to the peak to indicate the value of the embedded bit.

FIG. 5 includes the pseudocode in the form of a flowchart for the embedding process. The process
 20 begins by searching the original data until a positive peak that lies above a large threshold, labeled thr, and has a relatively small decrease after the peak, labeled dS, is found. This process is demonstrated in boxes **200**, **210** and **220**. The detection criteria are
 25 checked in the most computationally efficient order, which includes first checking to see if the point represent a peak since peaks are the least likely criterion.

When a desirable peak is found, the data point
 30 after the peak is adjusted according to a user defined bit depth, b, to carry the auxiliary information. Specifically, if it is the beginning of an auxiliary word, the synchronization code is embedded by adjusting the point after the peak, $x[n+1]$, to be equal to the
 35 peak, $x[n]$, minus half of the maximum allowable change,

$dS/2$, between the peak and the next point, as shown in
 boxes **242**, **230** and **250**. An auxiliary information bit
 of one is encoded by adjusting the point after the
 peak, $x[n+1]$, to be equal to the peak, $x[n]$, minus half
 5 the maximum change, $dS/2$, and plus the half the bit
 depth magnitude, 2^{b-1} . Correspondingly, an auxiliary
 information bit of zero is encoded by adjusting the
 point after the peak, $x[n+1]$, to be equal to the peak,
 $x[n]$, minus the sum of half the maximum change, $dS/2$,
 10 and half the bit depth magnitude, 2^{b-1} . This embedding
 of zeros and ones is shown in boxes **242**, **240**, **260**, **270**
 and **280**. The next two points after embedding the data
 should be skipped so one does not create another peak
 for very slow changing (i.e. flat) data, as shown in
 15 box **290**.

These steps are repeated until the auxiliary
 information, box **242** and **240**, has been hidden in the
 original data or the original data is finished.

FIG. 6 displays the pseudocode in the form of a
 20 flowchart for the retrieval process of the first
 preferred embodiment. The process begins by searching
 the original data is searched until a positive peak
 that lies above a large threshold, labeled thr , and has
 a relatively small decrease after the peak, labeled dS ,
 25 is found. This process is demonstrated in boxes **300**,
310 and **320**. Again, the search first looks for a peak
 to improve efficiency.

When a desirable peak is found, the difference
 between the peak and the data point after the peak is
 30 measured to retrieve the auxiliary information.
 Specifically, if the peak minus the point after the
 peak, $x[n]-x[n+1]$, is close to half of the maximum
 allowable change, $dS/2$, a new auxiliary word is
 beginning, as shown in boxes **330** and **350**. If the peak
 35 minus the point after the peak, $x[n]-x[n+1]$, is

approximately equal to half the maximum change, $dS/2$, minus half the bit depth magnitude, 2^{b-1} , an auxiliary bit of one is found. If this difference, $x[n]-x[n+1]$, is close to the sum of half the maximum change, $dS/2$, and half the bit depth magnitude, 2^{b-1} , an auxiliary bit of zero is retrieved. This retrieving of zeros and ones is shown in boxes **340**, **360**, **370**, **380**, and **382**. The two points immediately after retrieving the data can be skipped as shown in box **390**.

10 These steps are repeated until the auxiliary information has been retrieved in the original data or the original data is finished.

There are three user-defined parameters, including threshold, thr; bit depth, b; and maximum allowable change after the slope, dS. For 16 bit audio, the threshold is usually around 48 dB above the minimal quantization, as discussed above. For data with more bits per sample, the threshold may be increased to reduce perception. The bit depth is an indication of the relative change to be made to the sample point to embed the data. Thus, the smaller the bit depth, the less disturbance of the original data, making the embedded data less perceptible to the listener, but less robust, that is, more susceptible to being lost to noise or attack. Minimal perception in 16 bit audio is found when bit depths are between 1 and 6 bits. However, higher bit depths can be used if one desires more robustness to noise in trade for more perceptual degradation. The maximum allowable change after the peak, dS, must be at least the desired bit depth magnitude, 2^b . On the one hand, one can gain better robustness to noise at the expense of more distortion, if dS is set to twice the bit depth magnitude, 2^{b+1} . On the other hand, if one desires to keep the threshold undetectable to statistical cryptanalysis (labeled

statistically invisible), dS should be set at 2^b , and b should be small, probably below 3 bits. If dS is not 2^b , one can use the discrepancy of the average difference between large positive peaks and their next points between embedded file and regular file data to determine if the file contains embedded data or not. Finally, if dS is much greater than 2^b , the auxiliary information embedding rate will be increased, because more peaks will be found suitable for data embedding.

Using the principles explained above, skilled persons will be able to set the user-defined parameters to values appropriate to the requirements of a particular application.

As discussed above, the large threshold usually reduces the perceivable effect of adding the auxiliary information, and may even cause the auxiliary data to be non-perceivable, depending upon the data type. In addition, many data points satisfy the small difference between the peak and data point after the peak, because with a slope near 0 at the peak, the data is changing the least. This small difference means that the adjustment will be small as compared to the threshold, thus reducing the chance of perceiving the embedded auxiliary data

The pseudocode is shown using a buffer with what appears to be look ahead capabilities (i.e. $x[n+1]$). This makes the process easier to explain and understand. However, the process is causal, as determined by replacing $n+1$ with k , and keeping track of the last two points, $x[k-1]$ and $x[k-2]$.

Finally, one can add more criteria to define the peak. For example, the peak extends for one more point each direction where $x[n] > x[n-2]$, $x[n] > x[n+2]$, $x[n] > x[n-3]$, $x[n] > x[n+3]$, and so on, or the peak is of minimal sharpness, i.e. $x[n] - x[n-1] > 5$. Both of these

criteria produce better robustness to noise and less distortion since it will take more noise to move the location of the peak, although changes in the peak criteria affect the rate at which auxiliary data can be
 5 embedded.

The embedded data density and bit rate will vary with the original data and with the user-defined parameters. For example, bit rates of between 99 and 268 bits per second were achieved in CD quality audio
 10 data using a bit depth of 5 and a threshold of 5,000 (74 dB). Using a bit depth of 8 and maintaining a threshold at 5,000, the average embedding rate was 1,000 bits per second. When the threshold is lowered to 2,000 at a bit depth of 8, an average embedding rate of
 15 2,000 bits per second was found.

Embodiment 2

The second preferred embodiment hides the auxiliary information in large, steep threshold
 20 crossings which do not have a large change in slope. The method is more robust to noise changing the detected location. This occurs because it is less likely that noise changes the location of a threshold crossing as compared to a peak, since a threshold
 25 crossing usually has a slope larger than the slope at the peak, which, by definition, has a slope near zero. Testing with audio data has shown this embodiment, as compared to the first embodiment, to produce a lower embedded data rate and is more perceivable at a lower
 30 bit depth, in trade for the robustness to noise. One will probably find the optimal embodiment dependent upon the application.

FIG. 7 conceptually shows that data is embedded by setting the slope after the threshold crossing in
 35 relation to the slope at the threshold crossing.

In FIG. 8, the pseudocode for hiding the auxiliary information using the second preferred embodiment is presented in the form of a flow chart. The process begins by searching the original data until a positive,
 5 large, steep threshold (labeled thr) crossing with minimal change in slope (labeled dS) is found. This process is demonstrated in boxes **400**, **410** and **420**.

When the desirable threshold crossing is found, the data point after the threshold crossing is adjusted
 10 according to a user defined bit depth (b) to carry the auxiliary information in the change in slope. Note that the change in slope is defined as $(x[n+1]-x[n])-(x[n]-x[n-1])$, or equivalently as $x[n+1]-2*x[n]+x[n-1]$. Specifically, if it is the beginning of an auxiliary
 15 word, the synchronization code is embedded by adjusting the point after the threshold crossing, $x[n+1]$, so that the change in slope is zero, as shown in boxes **442**, **430** and **450**. An auxiliary bit of one is encoded by adjusting the point after the threshold crossing,
 20 $x[n+1]$, so that the change in slope is positive by an amount equal to half the bit depth magnitude, 2^{b-1} . Correspondingly, an auxiliary bit of zero is encoded by adjusting the point after the threshold crossing so that the change in slope is negative by an amount equal
 25 to half the bit depth magnitude, 2^{b-1} . This embedding of zeros and ones is shown in boxes **442**, **440**, **460**, **470** and **480**. The point after embedding the data can be skipped for efficiency as shown in box **490**.

These steps are repeated until the auxiliary
 30 information has been hidden in the original data or the original data is finished.

FIG. 9 shows the pseudocode in the form of a flowchart for the retrieval of the auxiliary information in the second preferred embodiment. The
 35 process begins by searching the original data until a

positive, large, steep threshold (labeled thr) crossing with minimal change in slope (labeled dS), is found.

This process is demonstrated in boxes **500**, **510** and **520**.

When a desirable threshold crossing is found, the
 5 change in slope around the threshold is measured to retrieve the auxiliary information. Again, the change in slope is defined as $(x[n+1]-x[n])-(x[n]-x[n-1])$, or equivalently as $x[n+1]-2*x[n]+x[n-1]$. Specifically, if the threshold crossing has almost zero change in slope,
 10 a new auxiliary word is begun, as shown in boxes **530** and **550**. If the threshold crossing has a positive change in slope approximately equal to half the bit depth magnitude, 2^{b-1} , an auxiliary bit of one is found. If the threshold crossing has a negative change in
 15 slope approximately equal to half the bit depth magnitude, 2^{b-1} , an auxiliary bit of zero is retrieved. This retrieving of zeros and ones is shown in boxes **540**, **560**, **570**, **580**, and **582**. The point after retrieving the data can be skipped for efficiency as
 20 shown in box **590**.

These steps are repeated until the auxiliary information has been retrieved in the original data or the original data is finished.

As mentioned above, one does not want the
 25 embedding process to eliminate the embedded location from fulfilling the detection criteria. Specifically, in this embodiment, the pre-threshold change condition, $x[n]-x[n-1]>dS+2^{b-1}$, in the detection criteria of box **420** and **520** requires that the adjustment of the next
 30 data point does not bring the point back below the threshold. An alternative approach, is to ignore this condition and to set either the current or next point ($x[n]$ or $x[n+1]$, respectively) to the threshold if the embedding process would cause the next point to move
 35 below the threshold, and ignore any data points that

are equal to the threshold in both the embedding and retrieving process. Interestingly, only when embedding a sync or 0 could the next point move below the threshold. Given these options, the described
 5 embodiment is chosen so the process is causal, thus incorporating the known advantages of causal processes.

Once again, the large threshold and maximum allowable change in slope condition, dS , reduce the perception of embedding the auxiliary data, and
 10 depending upon the data type can cause the embedding process to be completely non-perceivable. The maximum allowable change in slope condition, dS , can have any value. A larger value allows a higher data rate with more perceivable distortion, whereas a smaller value
 15 produces minimal distortion with a lower data rate. Our preferred setting for dS in 16 bit audio is equal to the bit depth magnitude, 2^b . Again, bit depths below 6 bits produce minimal distortion, but higher bit depths can be used for robustness to noise and attack.

20 Using a threshold of 2,000 (i.e. 66 dB) and a bit depth of 5, data rates between 40-100 bits per second are expected, with an average of about 75 bits per second, for CD quality audio. At a bit depth of 8, the bit rate increases to an average of 100 bits per
 25 second.

Modifications

The preferred embodiments have been described in detail above. However, there are many simple
 30 modifications that can be made to optimize the process for each use. Thus, these modifications and many similar ones produce a process that is equivalent to the one taught in this disclosure.

In some applications, a very simple embodiment
 35 could use a simple threshold to determine a local

masking opportunity and then encode the auxiliary data in the LSB of the point exceeding the threshold or of another point in the vicinity of the point exceeding the threshold. Such a variation is extremely simple, yet provides reduced perceptibility compared to prior art LSB schemes. As with the other embodiments, one must ensure that changing the value does not remove the point for the detection criterion. In this case, one could simply skip embedding where the change brings the data below the threshold, and change the current value of the data point to the threshold so that the data point will be skipped in the retrieving phase.

To increase the robustness of the invention to attack or noise, the following changes could be made. (Attack is defined as a person or machine trying to remove the auxiliary information from the combined signal without distorting the perception of the original data.)

Using a dynamic threshold can make it harder to remove the auxiliary information. An example dynamic threshold is an offset sinusoidal waveform. When using a dynamic threshold, dS should be small and close to 2^b so that the process does not change the distribution of the differences between neighboring points, i.e. be statistically invisible; thus, an attacker cannot use this data to find the threshold.

One can also use the statistical gaps when dS is larger than 2^b to find the threshold if the attack uses a DC shift. A DC shift is obviously a more potent attack for the second preferred embodiment than the first, but could affect the first preferred embodiment since threshold is one of the detection criteria.

The process could use more global definitions for peaks and threshold crossings, for better robustness to noise. Specifically, a peak or threshold crossing

definition that includes more points on each side.

Finally, the process can use any type of error correction in the auxiliary information to increase the robustness.

5 To increase the data rate, the following changes could be made. The auxiliary information does not need to include the extra sync pulses between the N-bit words, especially if robustness to noise is not needed. In addition, negative going peaks and/or more
10 thresholds can be used to increase bit rate. Finally, the process can use more than a binary system in adjusting the second bit to encode more information. However, the result is more likely to be perceivable or less robust to attack.

15 An interesting twist is to embed different auxiliary information on positive and negative peaks, and/or on various thresholds. In addition, with stereo files, you can code the channels separately or move between channels with consecutive points moving between
20 left and right channels.

A change that could improve the perception is to move the data point after the embedded point towards the value of the embedded point if combining the auxiliary information causes a large value change in
25 the embedded point.

As mentioned above, the data does not have to be relative to time. For example, the data could represent magnitude versus frequency. In addition, the data could be viewed as magnitude of a specific
30 frequency versus time. You could include all frequencies for an increased data rate. In other words, you could embed in the spectrum or spectrogram. Advantageously, you don't have to change the format of the given data to use this process and corresponding
35 apparatus.

For example, for bit-reduced data, such as MPEG compressed data. MPEG-compressed data comprises a series of data points that represent scaling factors and frequency coefficients. The invention could embed
5 auxiliary data in the series of MPEG data points, using, for example, one of the two embodiments described above. When using the first preferred embodiment, one may want to increase the peak or modify its LSB such that the term is only increased, rather
10 than decrease the point after the peak, such that quantization error is not increased in the MPEG data, especially when dealing with scaling factors. Skilled persons will recognize that, in using data like MPEG data that is divided into time frames, one could use,
15 for example, scaling factors or frequency coefficients from consecutive frames, as well as data points representing scaling factors and coefficients of different frequencies within a frame, when determining where to embed data. For example, the coefficients for
20 a particular frequency in consecutive frames could be considered as a series of consecutive data points, and those data points analyzed in accordance one of the embodiments above to determine where to embed data in the series. In an alternative example, the series of
25 data points representing scaling factors or frequency coefficients for different frequencies within a frame can be analyzed in accordance with the first or second embodiment above to decide where to embed data. The benefits of the inventions can be obtained using
30 any series of data points, which can be analyzed to determine where to embed data, although the degree of masking may vary depending upon what the data points represent.

Example Utilizations

Below are included some example utilizations of the algorithm to aid in its understanding. This list is not complete, and only highlights the usefulness of the invention. The invention in its various forms is useful in any application in which it is desirable to embed auxiliary data into original data in a minimally perceptible or imperceptible manner.

The process can be used to embed copyright information. This information could include a code to determine if the data can be copied. Copying devices, such as CD writers, could include an inexpensive integrated circuit that could interpret to embedded data and prohibit copying.

In addition, author's or artist's name and affiliation can be embedded. In this utilization, the auxiliary information is small and would be repeated over and over with synchronization pulses between each duplication. Alternatively, the copy code could be embedded using embodiment 1, and the creator's name and affiliation using embodiment 2.

The invention can also be used to send additional information. This information could be transmitted in ASCII or ANSI with 8 bit "words" (not to be included with digital words being defined as 32 bits) and synchronization pulses between these words, if desired. The information could be a secret message, lyrics to the song, or a description of the artwork. For lyrics, this could be useful for karaoke machines and CD or DVD players.

Digital Compression

The main problem with hiding data and digital compression (reducing bit rate not dynamic range) is that the process of hiding data is incompatible with

digital bit-rate reducing techniques known as compression (a.k.a. encoding and decoding). This incompatibility occurs since the goal of data hiding is to make the data minimally perceivable and the goal of
 5 compression is to remove minimally perceivable parts.

To this end, FIGs. 10A and B demonstrates the process for data hiding, if at some point the data must be compressed. For example, this may happen while transmitting the data.

10 In FIG. 10A, the auxiliary information is embedded in the non-compressed data using the described invented process or any other appropriate method, as shown in box **600**. Then, when the data needs to be compressed, the auxiliary information is retrieved via the
 15 described invention or the other appropriate method, and re-embedded in the compressed data with the described invented process or the other appropriate scheme, as shown in box **610**. The algorithm for data hiding in the compressed and non-compressed data may be
 20 the same algorithm, differing by only using different original data.

In FIG. 10B, the auxiliary information is retrieved from the compressed data using the described invented process or any other appropriate algorithm,
 25 the data is uncompressed, and the auxiliary information is embedded in the uncompressed data using the described invention or the other appropriate process, as shown in box **620**. Finally, when needed, the auxiliary information can be retrieved from the data
 30 using the described invention or the other appropriate algorithm, as shown in **630**. Once again, the algorithm for data hiding in the compressed and non-compressed data may be the same algorithm, differing by only using different original data.

Apparatus

As described above, FIG 2 demonstrates that the invented process can be implemented via logic processor and storage unit **18**. FIG. 12 shows the implementation with a digital processor **1200** and digital memory **1210**. The digital processor **1200** may be defined as the equivalent of a digital signal processor (DSP), general-purpose central processing unit (CPU), or a specialized CPU, including media processors. A likely DSP chip is one of the Texas Instruments TMS320 product line. A CPU could include one of Intel's Pentium line or Motorola/IBM's PowerPC product line. The design is straightforward for someone familiar with the state of the art given the pseudocode in Figs 5 through 9.

In addition, as shown in FIG. 13, a person familiar with the state of the art could implement the process with analog and digital circuitry, either separate or in an application specific integrated circuit (ASIC). The analog and digital circuitry could include any combination of the following devices: a digital-to-analog converter (D/A), comparators, sample-and-hold circuits, delay elements, analog-to-digital converter (A/D), and programmable logic controllers (PLC). Someone familiar with the state of the art given the previous description and pseudocode in FIGs. 5 through 9 could easily design the circuit.

FIG.s 11A and B show that the logic processor and storage unit typically comprise an embedding apparatus **700** and retrieving apparatus **770**. The embedding apparatus **700** includes the following. A data reader **710** to read original data **720** and auxiliary data **730**. A comparer **740**, that is, a circuit or device for comparing data points with known values or other data points. A data writer **750** to write the combined data **760** to a permanent or temporary storage media.

The retrieving apparatus **770** includes the following. A data reader **715** to read the combined data. The data reader **715** may be identical to the embedding data reader **710**, but it also may be
 5 different. A comparer **745**, that is, a circuit or device for comparing data points with known values or other data points and, if necessary, producing the auxiliary bit or bits. Once again the comparer **745** may be identical or different that the embedding comparer
 10 **740**. A data writer is not always necessary since the auxiliary information may be taken from memory or only displayed for the corresponding use.

Conclusions, Ramifications and Scope

15 As the reader can see from the description above and determined from testing the process with CD quality audio, this process and apparatus of hiding auxiliary information within original data is extremely efficient and has configurations which are non-perceivable.

20 These advantages are mainly due to the invented process finding locations to hide the auxiliary data without needing to transform the signal to the frequency domain and where masking may block or reduce the perception of the auxiliary data.

25 The foregoing descriptions of the preferred embodiments of the invention have been presented to teach those skilled in the art how to best utilize the invention. Many modifications and variations are possible in light of the above teaching. For example,
 30 as discussed above, the peak criteria can be extended, the threshold may be dynamic, synchronization codes, error correcting codes, and any combination of peaks and threshold can be used jointly. To this end, the following claims define the scope and spirit of the
 35 invention.

Claims

I claim:

1. A method of embedding auxiliary information within original data, the original data being divided into a series of groups, each group in the series characterized by a numerical value, the method comprising:
 - (a) investigating a first group to determine the presence of a local masking opportunity; and
 - (b) if the first group indicated the presence of a local masking opportunity, embedding data by setting the value of one or more groups in the neighborhood of the first group, including the first group, in accordance with the value of a portion of the auxiliary data,whereby allowing data to be embedded efficiently.
2. The method of claim 1 in which
 - (a) determining whether the first group represents a local masking opportunity includes examining the value of the first group and its relationship to a value of at least one other group near the first group; and
 - (b) embedding data by setting the value of one of the nearby groups includes setting a value dependent upon the value of the first group and on the value of the portion of auxiliary data.
3. The method of claim 1 in which
 - (a) determining whether a first group represents a local masking opportunity includes determining whether the first group
 - (i) exceeds a predetermined threshold;
 - (ii) is a peak; and
 - (iii) the second group value differs from the first group value by a predetermined amount;and

(b) embedding data by setting the value of the second group such that the difference between the first and second group are set by the portion of auxiliary data.

5 4. The method of claim 1 in which

(a) determining whether a first group represents a local masking opportunity includes determining whether

10 (i) the first group exceeds a predetermined threshold;

(ii) the previous group did not exceed the predetermined threshold;

15 (iii) the change in slope from the previous to the following group is less than another predetermined value; and

(iv) the difference between the first and previous group is less than yet another user defined value; and

20 (b) embedding data by setting the value of the second group such that the change in slope using the previous two group values is set by the portion of auxiliary data.

5. The method of claim 1 in which

25 (a) determining whether a first group represents a local masking opportunity includes determining whether the first group exceeds a threshold; and

(b) embedding data by setting the value of the first group includes changing the value of one or more bits of the first group.

30 6. The method of claim 1 in which each group represents a value of the same quantity measured at a different frequency.

35 7. The method of claim 1 in which nearby groups includes groups within 50 groups sequentially of the first group.

8. The method of claim 2 in which the original data represents the scaling factors or frequency coefficients of bit-rate reduced data, such as MPEG data.
- 5 9. The method of claim 2 in which each group represents a sample of audio data.
10. A method of retrieving auxiliary information within original data, the original data being divided into a series of groups, each group in the series
- 10 characterized by a numerical value, the method comprising:
- (a) investigating a first group to determine the presence of a local masking opportunity; and
 - (b) if the first group indicated the presence of a
- 15 local masking opportunity, retrieving data by measuring the value one or more groups in the neighborhood of the first group, including the first group,
- whereby allowing data to be retrieved efficiently.
- 20 11. The method of claim 10 in which
- (a) determining whether the first group represents a local masking opportunity includes examining the value of the first group and its relationship to a value of at least one other group near the first
- 25 group; and
- (b) retrieving data by setting the value of one of the nearby groups includes setting a value dependent upon the value of the first group and on the value of the portion of auxiliary data.
- 30 12. The method of claim 10 in which
- (a) determining whether a first group represents a local masking opportunity includes determining whether the first group
 - (i) exceeds a predetermined threshold;
 - (ii) is a peak; and
- 35

(iii) the second group value differs from the first group value by a predetermined amount; and

5 (b) retrieving data by setting the value of the second group such that the difference between the first and second group are set by the portion of auxiliary data.

13. The method of claim 10 in which

10 (a) determining whether a first group represents a local masking opportunity includes determining whether

(i) the first group exceeds a predetermined threshold;

15 (ii) the previous group did not exceed the predetermined threshold;

(iii) the change in slope from the previous to the following group is less than another predetermined value; and

20 (iv) the difference between the first and previous group is less than yet another user defined value; and

25 (b) retrieving data by setting the value of the second group such that the change in slope using the previous two group values is set by the portion of auxiliary data.

14. The method of claim 10 in which

(a) determining whether a first group represents a local masking opportunity includes determining whether the first group exceeds a threshold; and

30 (b) retrieving data by setting the value of the first group includes changing the value of one or more bits of the first group.

35 15. The method of claim 10 in which each group represents a value of the same quantity measured at a different frequency.

16. The method of claim 10 in which nearby groups includes groups within 50 groups sequentially of the first group.
17. The method of claim 11 in which the original data
5 represents the scaling factors or frequency coefficients of bit-rate reduced data, such as MPEG data.
18. The method of claim 11 in which each group represents a sample of audio.
- 10 19. An apparatus for performing the described data embedding or retrieving process comprising of
(a) a logic processor; and
(b) a storage unit,
whereby the logical processor and storage unit can
15 perform the described process.
20. The apparatus of claim 19 wherein the logic processor is digital processor and the storage unit is digital memory.
21. The apparatus of claim 19 wherein the logic
20 processor and the storage unit consists of a combination of analog and digital circuitry.
22. The apparatus of claim 19 used to embed auxiliary information wherein the logic processor and storage unit include
25 (a) a comparer device for comparing a group value in the series with a predetermined data and with at least one nearby group value to determine whether the group value represents a local masking opportunity;
30 (b) data writer for storing the original data and embedded data onto a storage media, the data writer changing a group value of the original data in the vicinity of the local masking opportunity to embed auxiliary data in the original data to
35 produce combined data, the local masking

opportunity reducing the likelihood of perception of the changed value when the combined data is presented to the user; and

- 5 (c) said comparer determining additional local masking opportunities and the data writer changing corresponding group values in the vicinity of the additional local masking opportunities until all the auxiliary data is embedded in the original data or until no additional local masking
- 10 opportunities are located or required.

23. The apparatus of claim 19 used to retrieve auxiliary information wherein the logic processor and storage unit include

- 15 (a) a comparer device for comparing a group value in the series with a predetermined data and with at least one nearby group value to determine whether the group value represents a local masking opportunity;
- (b) said comparer providing the auxiliary data from
- 20 the local masking opportunity; and
- (c) said comparer determining additional local masking opportunities and auxiliary information data bits

whereby the apparatus is efficient.

- 25 24. A method of bypassing removal of embedded data during digital bit-rate reduction (i.e. compression) which includes using separate data embedding techniques for non-compressed and compressed data.

- 30 25. The method of claim 24 in which the auxiliary information is not lost during the compression (a.k.a. encoding) by

- (a) retrieving the auxiliary information from the non-compressed data;
- (b) compressing the combined data; and

(c) re-embedding the auxiliary information using an appropriate technique in the compressed data, whereby the compressed data still has the auxiliary information embedded.

- 5 26. The method of claim 24 in which the auxiliary information is not lost during the decompression (a.k.a. decoding) by

(a) retrieving the auxiliary information from the compressed data using an appropriate technique;
10 (b) decompressing the compressed information; and
(c) embedding the auxiliary information in the non-compressed data,
whereby the non-compressed data still has the auxiliary information embedded.

- 15 27. A method of preventing unauthorized copying of audio data files, the audio data file being divided into a series of samples, each sample in the series characterized by a numerical value, the method comprising:

20 (a) determining whether a first sample represents a local masking opportunity by examining the value of the first sample and values of at least one other sample near the first sample;
(b) if the first sample represents a local masking
25 opportunity, embedding a portion of unauthorized copy prevention data by setting the value of one of the nearby groups in accordance with the value of a portion of the copy prevention data, the local masking opportunity allowing the portion of
30 the unauthorized copy prevention data to be embedded with minimal perception by a user of the audio file;
(c) locating additional local masking opportunities to embed additional unauthorized copy prevention
35 data within the audio data file; and

(d) upon attempting to copy the audio data,
verifying whether the combined data includes copy
prevention information and, if so, preventing a
copy from being produced.

Abstract of the Disclosure

This patent application demonstrates a process and apparatus for hiding auxiliary information within original data such that the process is extremely
5 efficient and minimally perceived by humans, known as watermarking or steganography. One use of this hidden data is to copyright digital media, including audio, images or video, to stop this illegal duplication process. The invented process involves using detection
10 criteria within the original data to adjust neighboring data to carry the auxiliary information. The detection criteria allow the process to find locations to embed the data where masking reduces its perception without the complex transformations, such as those to the
15 frequency domain. The process can be adjusted according to the desired tradeoffs between perception, coding rate and robustness to attack. To this end, the process can be implemented at a much lower cost than competing algorithms usually with less degradation in
20 quality.




Fig 1




Fig. 2




Fig. 12

A to D Converter	Sample and Hold	D to A Converter
Comparator	PLC	Delays

Fig 13




Fig 3




Fig. 10A




Fig. 10B




Fig. 4



Fig. 7




Fig. 5




Fig. 6




Fig. 8




Fig. 9




Fig. 11A





Fig. 11B

Please type a plus sign (+) inside this box → 

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)	Attorney Docket Number	Levy 1R	
	First Named Inventor	Kenneth Levy	
	COMPLETE IF KNOWN		
	Application Number	/	
	Filing Date	Sept 23, 1999	
	Group Art Unit		
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing	<input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	Examiner Name	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Method And Apparatus For Embedding Auxiliary Information Within Original Data.

the specification of which (Title of the Invention)

☒ is attached hereto
OR

☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International

Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.
#60/101,851	9/25/98	
#60/110,683	12/02/98	
#60/114,725	12/31/98	
#60/126,591	3/26/99	

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☒

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☐ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name	Registration Number	Name	Registration Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label

OR ☒ Correspondence address below

Name	Ken Levy, AIPL				
Address	110 NE Cedar Street				
Address					
City	Stevenson	State	WA	ZIP	98648
Country	USA	Telephone	509-427-5374	Fax	509-427-7101

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))		Family Name or Surname	
Kenneth Lee		Levy	
Inventor's Signature		Date	7/23/97
Residence: City	Stevenson	State	WA
		Country	USA
Post Office Address	110 NE Cedar Street		
Post Office Address			
City	Stevenson	State	WA
		ZIP	98648
		Country	USA

☐ Additional inventors are being named on the supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto